


Raccordi Femmina Sede JIC 37°

JIC Females 37° Cone

JIC 37° Dichtkegel

ISO 12151-5 (ISO 8434-2)

DKJ



	CODICE Part n° Bestell-Nr.	Filetto Thread Gewinde	Ø F ø F ø F	DN Tubo DN Hose DN Schlauch	CH	L	Ø C	H	M
a	S 30 43 0 604 005 H	7/16" -20 UNF		3/16" 05	14	45,5	3	23,5	14
a	S 30 43 0 604 006 H	7/16" -20 UNF		1/4" 06	14	51,5	4	23,5	14
a	S 30 43 0 606 006 H	1/2" -20 UNF		1/4" 06	17	52,5	4	24,5	15
a	S 30 43 0 606 008 H	1/2" -20 UNF		5/16" 08	17	52,5	5,5	24,5	15
a	S 30 43 0 608 006 S	9/16" -18 UNF		1/4" 06	19	54,5	4	26,5	16,5
a	S 30 43 0 608 008	9/16" -18 UNF		5/16" 08	19	55	5,5	27	17
a	S 30 43 0 608 010	9/16" -18 UNF		3/8" 10	19	56	7	26,5	16,5
a	S 30 43 0 610 010	3/4" -16 UNF		3/8" 10	24	60	7	30,5	19
a	S 30 43 0 610 013 A	3/4" -16 UNF		1/2" 12	24	59,5	9,5	30	18,5
NEW	S 30 43 0 610 016	3/4" -16 UNF		5/8" 16	24	64,5	12,5	31,5	20
NEW	S 30 43 0 610 019	3/4" -16 UNF		3/4" 19	24	72,5	15	33,5	22
a	S 30 43 0 613 019	7/8" -14 UNF		3/4" 19	27	75,5	15	36,5	23,5
a	S 30 43 0 613 010	7/8" -14 UNF		3/8" 10	27	63	7	33,5	20
a	S 30 43 0 613 013 A	7/8" -14 UNF		1/2" 12	27	64,5	9,5	35	21
NEW	S 30 43 0 613 016 A	7/8" -14 UNF		5/8" 16	27	67,5	12,5	33,5	19,5
NEW	S 30 43 0 613 019	7/8" -14 UNF		3/4" 19	27	75,5	15	36,5	23,5
a	S 30 43 0 619 013 A	1 1/16" - 12 UN		1/2" 12	32	67	9,5	37,5	21,5
a	S 30 43 0 619 016 A	1 1/16" - 12 UN		5/8" 16	32	72	12,5	38	22
a	S 30 43 0 619 019 A	1 1/16" - 12 UN		3/4" 19	32	79	15	40	24
a	S 30 43 0 619 025 A	1 1/16" - 12 UN		1" 25	32	87	15	40	24
a	S 30 43 0 622 019 A	1 3/16" - 12 UN		3/4" 19	36	80,5	15	41,5	25
a	S 30 43 0 625 019 A	1 5/16" - 12 UN		3/4" 19	41	81	15	42	25
a	S 30 43 0 625 025 A	1 5/16" - 12 UN		1" 25	41	89	19,5	42	25
a	S 30 43 0 632 025 A	1 5/8" - 12 UN		1" 25	50	90,5	19,5	43,5	27
a	S 30 43 0 632 032 A	1 5/8" - 12 UN		1 1/4" 31	50	98,5	26	44	27,5
a	S 30 43 0 638 032 A	1 7/8" - 12 UN		1 1/4" 31	60	103,5	26	49	29,5
a	S 30 43 0 638 038 A	1 7/8" - 12 UN		1 1/2" 38	60	107	32	49	29,5
a	S 30 43 0 650 050 A	2 1/2" - 12 UN		2" 51	75	131,5	42	59	35,5

a: dado pressato


a: crimped nut

a: verkrimpte Überwurfmutter

Raccordi Femmina Sede JIC 37°
JIC Females 37° Cone
JIC 37° Dichtkegel


ISO 12151-5 (ISO 8434-2)

DKJ 90



	CODICE Part n° Bestell-Nr.	Filetto Thread Gewinde	Ø F ø F ø F	DN Tubo DN Hose DN Schlauch	CH	L	Ø C	H	M
a	S 30 52 0 604 005 H	7/16" - 20 UNF		3/16" 05	14	47,5	3	26	25,5
a	S 30 52 0 604 006 H	7/16" - 20 UNF		1/4" 06	14	57	4	26	29
a	S 30 52 0 606 006 H	1/2" - 20 UNF		1/4" 06	17	57	4	27	29
a	S 30 52 0 608 006 A	9/16" - 18 UNF		1/4" 06	19	57	4	28	29
a	S 30 52 0 608 008 A	9/16" - 18 UNF		5/16" 08	19	57,5	5,5	30,5	29,5
a	S 30 52 0 608 010 A	9/16" - 18 UNF		3/8" 10	19	63	7	35	33,5
a	S 30 52 0 610 010 A	3/4" - 16 UNF		3/8" 10	24	63	7	37	33,5
a	S 30 52 0 610 013 A	3/4" - 16 UNF		1/2" 12	24	71,5	9,5	42,5	42
a	S 30 52 0 613 010 A	7/8" - 14 UNF		3/8" 10	27	63	7	38	33,5
a	S 30 52 0 613 013 A	7/8" - 14 UNF		1/2" 12	27	71,5	9,5	43,5	42
a	S 30 52 0 613 016 A	7/8" - 14 UNF		5/8" 16	27	87	12,5	54	53
a	S 30 52 0 619 013 A	1 1/16" - 12 UN		1/2" 12	32	71,5	9,5	45	42
a	S 30 52 0 619 016 A	1 1/16" - 12 UN		5/8" 16	32	87	12,5	54,5	53
a	S 30 52 0 619 019 A	1 1/16" - 12 UN		3/4" 19	32	97	15	56	58
a	S 30 52 0 622 019 A	1 3/16" - 12 UN		3/4" 19	36	99	15	58,5	60
a	S 30 52 0 625 019 A	1 5/16" - 12 UN		3/4" 19	41	99	15	58,5	60
a	S 30 52 0 625 025 A	1 5/16" - 12 UN		1" 25	41	126	19,5	70,5	79
a	S 30 52 0 632 025 A	1 5/8" - 12 UN		1" 25	50	126	19,5	72,5	79
a	S 30 52 0 632 032 A	1 5/8" - 12 UN		1 1/4" 31	50	150,5	26	86	96
a	S 30 52 0 638 032 A	1 7/8" - 12 UN		1 1/4" 31	60	150,5	26	87	96
a	S 30 52 0 638 038 A	1 7/8" - 12 UN		1 1/2" 38	60	175,5	32	100,5	117,5
a	S 30 52 0 650 050 A	2 1/2" - 12 UN		2" 51	75	216,5	42	135	144

DKJ 45



a	S 30 82 0 604 006 A	7/16" - 20 UNF		1/4" 06	14	61,5	4	12,5	33,5
a	S 30 82 0 606 006 H	1/2" - 20 UNF		1/4" 06	17	62	4	13,5	34
a	S 30 82 0 608 006 A	9/16" - 18 UNF		1/4" 06	19	62,5	4	14	34,5
a	S 30 82 0 608 008 A	9/16" - 18 UNF		5/16" 08	19	64	5,5	15	36
a	S 30 82 0 608 010 A	9/16" - 18 UNF		3/8" 10	19	70,5	7	17,5	41
a	S 30 82 0 610 010 A	3/4" - 16 UNF		3/8" 10	24	72	7	19	42,5
a	S 30 82 0 610 013 A	3/4" - 16 UNF		1/2" 12	24	80,5	9,5	20,5	51
a	S 30 82 0 613 010 A	7/8" - 14 UNF		3/8" 10	27	72,5	7	19,5	43
a	S 30 82 0 613 013 A	7/8" - 14 UNF		1/2" 12	27	81,5	9,5	21,5	52
a	S 30 82 0 613 016 A	7/8" - 14 UNF		5/8" 16	27	96,5	12,5	25,5	62,5
a	S 30 82 0 619 013 A	1 1/16" - 12 UN		1/2" 12	32	82,5	9,5	22,5	53
a	S 30 82 0 619 016 A	1 1/16" - 12 UN		5/8" 16	32	97	12,5	26	63
a	S 30 82 0 619 019 A	1 1/16" - 12 UN		3/4" 19	32	108	15	28,5	69
a	S 30 82 0 622 019 A	1 3/16" - 12 UN		3/4" 19	36	108,5	15	29	69,5
a	S 30 82 0 625 019 A	1 5/16" - 12 UN		3/4" 19	41	108,5	15	29	69,5
a	S 30 82 0 625 025 A	1 5/16" - 12 UN		1" 25	41	134,5	19,5	32,5	87,5
a	S 30 82 0 632 025 A	1 5/8" - 12 UN		1" 25	50	135,5	19,5	34	88,5
a	S 30 82 0 632 032 A	1 5/8" - 12 UN		1 1/4" 31	50	161	26	41	106,5
a	S 30 82 0 638 032 A	1 7/8" - 12 UN		1 1/4" 31	60	162	26	42	107,5
a	S 30 82 0 638 038 A	1 7/8" - 12 UN		1 1/2" 38	60	184,5	32	46,5	126,5
a	S 30 82 0 650 050 A	2 1/2" - 12 UN		2" 51	75	231	42	67	158,5

a: dado pressato

a: crimped nut

a: verkrimpte Überwurfmutter

Articoli di basso consumo su richiesta

Slow moving articles available on request

Artikel mit geringen Stückzahlen auf Anfrage